

Awning Window Series

Product Features

STANDARD FEATURES (operating unit):

- Natural, eastern white pine
- Frame construction design for 3 1/2" jambs
- Clear insulated glass
- Choice of black, grey or aluminum spacer bar
- EM600 casing & 566 subsill

SPECIFICATIONS:

FRAME:

- 1 1/16" thick X 3 1/2" width/base jamb in pine (or other wood species).
- Jamb extension is 21/32" thick and is available up to 16" wide.
- Frame is manufactured with Bulb weather-strip (white or beige).

SASH:

- 1 5/8" thick in pine (or other wood species).
- Interior profiling is ovalo, restoration, or square
- Sash is manufactured with Polyflex weather-strip (white or beige).

OPTIONS:

- 2 1/4" thick sash in clear pine is also available (or other wood species).
- Interior profiling on 2 1/4" thick sash is Heritage or Legacy profile.

HARDWARE:

Multipoint from ROTO – multipoint lock & escutcheon plate, roto-gear, foldaway handle and friction hinges.

- White (standard finish)
- Oil rubbed bronze
- Antique brass
- Pewter
- Brass
- Brush chrome
- Black
- Brushed nickel
- Bright chrome
- Faux Oil Rub Bronze

Motorized hardware is also available. Sentry II operator and switch with optional remote control. Please contact a Norwood sales representative for more information and pricing.

SCREENS: (aluminum) – Interior application

- White (standard)
- Coppertone (standard)
- Brown
- Black
- Beige
- Ivory
- Green
- Mill finish
- Norcoat finish

Aluminum screens are manufactured with 90 degree; also available are concealed 45 degree corners. (Note: Visible corner key will not match Norcoat finish) Black, grey fiberglass mesh & Crystal Clear screen mesh available. Aluminum mesh is available upon request.

Awning Window Series

SCREENS (wood) – interior application:

Wood screens are available as stationary or swinging in clear solid pine, finger joint pine or mahogany wood species. Other wood species are available upon request. Hinge & screen knob finishes are limited. Please contact a Norwood sales representative for more information.

SCREENS (roll-down) interior application:

- Roll-down screens match interior wood species
- Minimum 6 9/16" jamb and custom stiles & rails are required for this screen application.
- Roll down screens add 7/8" to RO height.
- Norwood recommends the use of a minimum 2 1/2" wide casing for this application

GRILLES:

SIMULATED DIVIDED LITE (SDL):

SDL available in putty & ovalo, 7/8" and 1 1/4" are Standard. Many more options are available – see Grille Section details.

TRUE DIVIDED LITE (TDL):

- - 15/16"
- - 1 1/4"
- - 1 3/4"
- - 2"
- - 2 1/4"

TDL is only available in restoration profile.

ALUMINUM GRILLES:

- Aluminum grilles are located between the glass and only available as rectangular. These grilles are available in white or white Georgian.
- Pencil grilles are located between the glass and are available in 3/8" pewter or brass.

LEAD OVERLAY:

- 1/4"
- 3/8"
- 1/2"

Lead overlay can be applied to one or multiple faces of glass, however, cannot be applied to the low-e surface. Lead overlay is available in patina or silver lead. Custom patterns are available upon request.