

Folding Doors Series

Product Features

STANDARD FEATURES- L&S:

- Natural or eastern white pine
- 1 3/4" thick door panel
- 6 9/16" jamb
- Tempered clear glass
- Ovalo profile
- Capri bright brass multi point hardware & hinges
- 4 19/32" stiles & head rail, 7 3/8" sill rail
- Bronze anodized sill
- EM600 casing
- Inswing or outswing (please note that there is no warranty on weather infiltration on inswing units)

SPECIFICATIONS:

FRAME:

- 1 1/16" thick X 6 9/16" width/base jamb with clear solid interior & finger-joint pine exterior (or other wood species).
- Jamb extension is 21/32" thick and is available up to 10 1/4" wide (some restrictions apply).
- Frame is manufactured with compression weather-strip (black or beige).
- Maximum panel width is 39" and minimum frame width is 24" on operating unit.
- Maximum panel height is 120" on operating unit.
- Maximum number of door panels is eight each way.

DOOR PANEL:

- 1 3/4" or 2 1/4" thick door panel with clear pine interior & exterior, finger-joint edges (please note that clear solid pine or other wood species will have clear solid edges).
- 4 19/32" stiles & head rails with 7 3/8" sill rail is standard on 1 3/4" thick folding door panel (custom stile & rail sizes available – some restrictions apply)
- 5 5/8" stiles & head rails with 9 1/4" sill rail is standard on 1 3/4" thick front entry door panel (custom stile & rail sizes available – some restrictions apply)

HARDWARE:

Capri, Allegro, Romance & Viking handle styles from Ferco.

- Bright brass (standard finish)
- Oil rubbed bronze
- Antique brass
- Pewter
- Brush chrome
- Bronze
- Bright chrome
- Black (only available in Romance & Viking style)

Hinges, door pulls, magnets and flush bolts are only available in stainless steel, PVD brass & bronze powder coat and may not be an exact match to the handle finish.

Folding Doors Series

Product Features

GRILLES:

SIMULATED DIVIDED LITE (SDL):

Exterior sdl available in putty & ovalo, 7/8" and 1'1/4" are Standard. Many more options are available – see Grille Section details.

ALUMINUM GRILLES:

Aluminum grilles are located between the glass and are available rectangular. These grilles are available in white or white Georgian.

Pencil grilles are located between the glass and are available in 3/8" pewter or brass.

LEAD OVERLAY:

- 1/4"
- 3/8"
- 1/2"

Lead overlay can be applied to one or multiple faces of glass, however, cannot be applied to the low e surface. Lead overlay is available in patina or silver lead. Custom patterns are available upon request.