

French Door

Product Features – Single French & Front Entry

STANDARD FEATURES (FD):

- Natural eastern white pine frame & panels
- 1 3/4" thick door panel
- 4 9/16" jamb
- Tempered clear glass
- Ovalo profile
- Capri bright brass multi point hardware & hinges
- 4 19/32" stiles & head rail, 7 3/8" sill rail
- Bronze anodized sill c/w clear coat oak crown
- EM600 casing
- Inswing or outswing

STANDARD FEATURES (FD):

- Natural eastern white pine
- 1 3/4" thick door panel
- 4 9/16" jamb
- Ovalo profile
- Tempered clear glass
- Capri bright brass multi point hardware & hinges
- 5 5/8" stiles & head rail, 9 1/4" sill rail
- Bronze anodized sill c/w clear coat oak crown
- EM600 casing
- Inswing or outswing

STYLES:

French doors are also available as half-round, camber top (center facing, left & right facing), quarter round & gothic. Custom styles available, Please contact a Norwood representative for more information.

SPECIFICATIONS:

FRAME:

- 1 3/16" thick X 4 9/16" width/base jamb with clear solid interior & finger-joint pine exterior (or other wood species). Option for 1 3/4" thick jamb is available.
- ~ Jamb extension is 1 1/64" thick on inswing & 21/32" thick on outswing and is available up to 10 1/4" wide (some restrictions apply).
- ~ Frame is manufactured with compression weather-strip (black or beige).
- ~ 5 5/8" bronze anodized sill on 4 9/16" base jamb.
- ~ Bronze anodized sill extensions available up to 11 7/8" (some restrictions apply)
- ~ Bronze anodized low profile (handicap) sill available on outswing doors only.
- ~ Maximum frame width is 43 9/16" and minimum frame width is 20" on operating unit.
- ~ Maximum frame height is 120" and minimum frame height is 75" on operating unit.

PANEL:

- 1 3/4" or 2 1/4" thick door panel with clear pine interior & exterior, finger-joint edges (please note that clear solid pine or other wood species will have clear solid edges).
- 4 19/32" stiles & head rails with 7 3/8" sill rail is standard on 1 3/4" thick French door panel (custom stile & rail sizes available – some restrictions apply)
- 5 5/8" stiles & head rail with 9 1/4" sill rail is standard on 1 3/4" thick Front entry door panel (custom stile & rail sizes available – some restrictions apply).
- Inswing door panel is c/w wood drip cap (edge) & dark bronze sweep.

HARDWARE:

Capri, Allegro, Romance & Viking handle styles from Ferco.

- Bright brass (standard finish)
- Oil rubbed bronze
- Antique brass
- Pewter
- Brush chrome
- Bronze
- Bright chrome
- Black (only available in Romance & Viking style)
- Doors under 89" in height will have three hinges and 89" and over will have four hinges. Please note that Romance & Viking handles are only available in pewter & black finishes. Adjustable hinges and single point lock are available. Please contact a Norwood representative for more information.

SCREENS: (wood swinging c/w hinges only):

- Wood swinging screens are available on inswing & outswing doors.
- 1 1/4" or 1 3/4" thick
- 6 9/16" min. jamb required for 1 1/4" thick screen panel & 7 1/16" min. jamb required for 1-3/4" thick screen panel.
- Option to match DLO of door panel.
- Single pane tempered storm insert available.
- Hinges are available in oil rubbed bronze, brass & stainless.

GRILLES:

SIMULATED DIVIDED LITE (SDL):

SDL available in putty & ovalo, 7/8" and 1 1/4" are Standard. Many more options are available – see Grille Section details.

TRUE DIVIDED LITE (TDL):

- - 15/16"
- - 1 1/4"
- - 1 3/4"
- - 2"
- - 2 1/4"

TDL is only available in restoration profile.

ALUMINUM GRILLES:

- Aluminum grilles are located between the glass and only available as rectangular. These grilles are available in white or white Georgian.
- Pencil grilles are located between the glass and are available in 3/8" pewter or brass.

LEAD OVERLAY:

- 1/4"
- 3/8"
- 1/2"

Lead overlay can be applied to one or multiple faces of glass, however, cannot be applied to the low-e surface. Lead overlay is available in patina or silver lead. Custom patterns are available upon request.

Sliding Patio Door
