

Sliding Patio Door

Product Features

STANDARD FEATURES (operating unit):

- Natural eastern white pine frame & panels
- One operating panel & one fixed panel with regular patio door stiles & rails
- 4 5/8" jamb
- Brass handle
- White or coppertone sliding screen & hardware
- Tempered clear glass
- Ovalo interior profiling
- Bronze anodized sill
- EM600 casing

STYLES:

Casement Windows Casement windows are available as casement bays & bows, camber top (center facing, left & right facing), extended half round, segmental, polygon shapes, elliptical, and gothic.

SPECIFICATIONS:

FRAME:

- 1 7/16" thick X 5 9/16" width/base jamb with clear solid interior & finger-joint pine exterior (or other wood species).
- Frame is manufactured with fin-seal pile weather stripping & Schlegal pile running the full perimeter.
- Jamb extension available up to 10 1/4" (some restrictions apply).
- Dual sliding panels with no center post (one frame) option available with maximum width of 168" with french stiles & rails.
- Custom heights up to 96" are available with french stiles and rails only.
- White or coppertone sliding screen with brass handle.

PANEL:

- 1 3/4" thick door panels with clear pine interior & exterior, finger-joint edges (please note that clear solid pine or other wood species will have clear solid edges).
- Standard stiles & rails on;
- Operating panel – head & sill @ 3 1/4", stile on lock side @ 4 9/16", stile on meeting rail @ 1 7/8"
- Fixed panel – head @ 4 1/16", sill @ 3 15/16, stiles @ 4 9/16"
- French stiles & rails on;
- Operating panel – head @ 4 9/16", sill @ 7 3/8", stiles @ 4 9/16"
- Fixed panel – head @ 5 3/8", sill @ 8 1/8", stiles @ 4 9/16"
- Tandem steel ball rollers

HARDWARE:

- Standard C- handle with exterior cylinder lock.
- Brass (standard)
- Antique brass
- Brushed chrome
- Patio door limiters (foot bolt) in bronze or white finish are available. Application is on bottom of operating panel on interior. Please contact a Norwood representative for more information.

SCREENS: (aluminum) – Interior application

- White (standard)
- Coppertone (standard)
- Option to match norcoat color

Sliding Patio Door

GRILLES:

SIMULATED DIVIDED LITE (SDL):

SDL available in putty & ovalo, 7/8" and 1'1/4" are Standard. Many more options are available – see Grille Section details.

TRUE DIVIDED LITE (TDL):

- - 15/16"
- - 1 1/4"
- - 1 3/4"
- - 2"
- - 2 1/4"

TDL is only available in restoration profile.

ALUMINUM GRILLES:

- Aluminum grilles are located between the glass and only available as rectangular. These grilles are available in white or white Georgian.
- Pencil grilles are located between the glass and are available in 3/8" pewter or brass.

LEAD OVERLAY:

- 1/4"
- 3/8"
- 1/2"

Lead overlay can be applied to one or multiple faces of glass, however, cannot be applied to the low-e surface. Lead overlay is available in patina or silver lead. Custom patterns are available upon request.