

Transom Specifications

Product Features

STANDARD FEATURES (operating unit):

- Natural, eastern white pine
- Frame construction design for 3 1/2" jambs
- Clear insulated glass
- Choice of black, grey or aluminum spacer bar
- EM600 casing & 566 subsill

STYLES:

Casement Windows Casement windows are available as casement bays & bows, camber top (center facing, left & right facing), extended half round, segmental, polygon shapes, elliptical and gothic.

SPECIFICATIONS:

FRAME:

- 11/16" thick X 3 1/2" width/base jamb in pine (or other wood species).
- Jamb extension is 21/32" thick and is available up to 16" wide.
- Frame is manufactured with Bulb weather-strip (white or beige).

SASH:

- 1 5/8" thick in pine (or other wood species).
- Interior profiling is ovalo, restoration, or square
- 1-9/16" stiles & rails
- Sash is manufactured with Polyflex weather-strip (white or beige).

OPTIONS:

- 2 1/4" thick sash in clear pine is also available (or other wood species).
- Interior profiling on 2 1/4" thick sash is Heritage or Legacy profile.

SIMULATED DIVIDED LITE (SDL):

SDL available in putty & ovalo, 7/8" and 1 1/4" are Standard. Many more options are available – see Grille Section details.

TRUE DIVIDED LITE (TDL):

- - 15/16"
- - 1 1/4"
- - 1 3/4"
- - 2"
- - 2 1/4"

TDL is only available in restoration profile.

ALUMINUM GRILLES:

- Aluminum grilles are located between the glass and only available as rectangular. These grilles are available in white or white Georgian.
- Pencil grilles are located between the glass and are available in 3/8" pewter or brass.

LEAD OVERLAY:

- 1/4"
- 3/8"
- 1/2"

Lead overlay can be applied to one or multiple faces of glass, however, cannot be applied to the low-e surface. Lead overlay is available in patina or silver lead. Custom patterns are available upon request.