

# NORWOOD

WINDOWS & DOORS

## Norclad Awning Single Units Elevation Chart

	14-3/4"	18-11/16"	22-5/8"	26-9/16"	30-1/2"	34-7/16"	42-5/16"
	15-21/32"	19-19/32"	23-17/32"	27-15/32"	31-13/32"	35-11/32"	43-7/32"
	22-7/16"	26-13/32"	30-11/32"	34-9/32"	38-7/32"	42-5/32"	50-1/32"
	20-11/16"	24-5/8"	28-9/16"	32-1/2"	36-7/16"	40-3/8"	48-1/4"
	19-11/16"	23-5/8"	27-9/16"	31-1/2"	35-7/16"	39-3/8"	47-1/4"

  

	13-13/16"	14-23/32"	22-5/16"	20-15/16"	19-11/16"	
	17-3/4"	18-21/32"	26-1/2"	24-7/8"	23-5/8"	
	25-5/8"	26-17/32"	34-1/8"	32-3/4"	31-1/2"	
	29-9/16"	30-15/32"	38-1/16"	36-11/16"	35-7/16"	
	33-1/2"	34-13/32"	42"	40-5/8"	39-3/8"	

  

	AW0505	AW0605	AW0705	AW0805	AW0905	AW1005	AW1205
	AW0506	AW0606	AW0706	AW0806	AW0906	AW1006	AW1206
	AW0508	AW0608	AW0708	AW0808	AW0908	AW1008	AW1208
	AW0509	AW0609	AW0709	AW0809	AW0909	AW1009	AW1209
	AW0510	AW0610	AW0710	AW0810	AW0910	AW1010	AW1210

**Notes:**

R.S.O. for additional combinations is the unit width or height plus 1".

M.O. for additional combinations is the brick mold width or height plus 1/2".

R.S.O. for stacked combinations mulled two or more wide and over 84" in width or height, it is recommended to add a filler for each stacked layer in height. Thickness of the filler may vary due to dimensions of the overall unit.