

# Awning Window Series

---

## Product Features

### **STANDARD FEATURES** (Fixed unit):

- ~ Natural or prime time 2, eastern white pine (clear interior/finger joint exterior)
- ~ Frame construction design for 3 1/2" jambs
- ~ Clear insulated glass
- ~ Choice of black, grey or aluminum spacer bar
- ~ EM600 & 566 subsill

### **SPECIFICATIONS:**

#### **FRAME:**

- ~ 11/16" thick X 3 1/2" width/base jamb in pine (or other wood species).
- ~ Jamb extension is 21/32" thick and is available up to 16" wide.
- ~ Frame is manufactured with Bulb weather-strip (white or beige).

#### **SASH:**

- ~ 1 5/8" thick in clear pine (or other wood species).
- ~ Interior profiling is ovalo or restoration profile.
- ~ Sash is manufactured with Polyflex weather-strip (white or black).

#### **OPTIONS:**

- ~ 2 1/4" thick sash in clear pine is also available (or other wood species).
- ~ Interior profiling on 2 1/4" thick sash is Heritage or Legacy profile.

#### **HARDWARE:**

Multipoint lock & escutcheon plate, roto-gear & foldaway handle.

- ~ White (standard finish)
- ~ Oil rubbed bronze
- ~ Antique brass
- ~ Pewter
- ~ Brass
- ~ Brushed Chrome
- ~ Black
- ~ Brushed nickel
- ~ Chrome
- ~ Faux Oil Rub Bronze

Motorized hardware is also available. Sentry II operator and switch with optional remote control. Please contact a Norwood sales representative for more information and pricing.

**SCREENS** (aluminum bars) interior application:

- ~ White (standard)
- ~ Coppertone (standard)
- ~ Brown
- ~ Black
- ~ Beige
- ~ Ivory
- ~ Green
- ~ Mill finish
- ~ Norcoat finish

**SCREEN MESH** Black fiberglass as Standard

- ~ Other options: Crystal Clear, Grey fiberglass
- ~ Aluminum: Black, Grey and Bronze

**SCREENS** (wood) – interior application:

Wood screens are available as stationary or swinging in clear solid pine, finger joint pine or mahogany wood species. Other wood species are available upon request. Hinge & screen knob finishes are limited. Please contact a Norwood sales representative for more information.

**SCREENS** (roll down) – interior application:

- ~ Roll down screens available in all wood species.
- ~ Minimum 6 9/16" jamb and custom stiles & rails are required for this screen application.
- ~ Roll down screens add 7/8" to RO height.
- ~ Norwood recommends the use of a minimum 2 1/2" wide casing for this application

**GRILLES:**

**SIMULATED DIVIDED LITE (SDL):**

SDL available in putty & ovalo 7/8" and 1 1/4" are Standard.  
Other widths and profiles are available – See grille section details.

**TRUE DIVIDED LITE:**

Contact a Norwood sales representative for prices and availability  
TDL is available with restoration & heritage profiles.

**LEAD OVERLAY:**

- ~ 1/4"
- ~ 3/8"
- ~ 1/2"

Lead overlay can be applied to one or multiple faces of glass, however, cannot be applied to the low-e surface. Lead overlay is available in patina or silver lead. Custom patterns are available upon request.