

Spec Sheet French Outswing

Casement Wood Series

Product Features

STANDARD FEATURES:

- ~ Natural, Polyurea Prime, Norcoat or Stain, eastern white pine
- ~ Frame construction design for 3 1/2" jamba
- ~ Clear insulated glass
- ~ Choice of black, grey or aluminum spacer bar
- ~ EM600 & 566 subsill

STYLES:

French Outswing Casement windows are available as single or double units & camber top (center facing). Please contact a Norwood sales representative for further information on decorative shapes.

SPECIFICATIONS:

FRAME:

- ~ 1 1/16" thick X 3 1/2" width/base jamb in pine (or other wood species).
- ~ Jamb extension is 21/32" thick and is available up to 16" wide.
- ~ Frame is manufactured with Bulb weather-strip (white or beige).

SASH:

- ~ 1 3/4" thick in clear pine (or other wood species).
- ~ Interior profiling is restoration profile.
- ~ Sash is manufactured with Bulb weather-strip (white or black)

HARDWARE:

Melron handle with multipoint lock with friction hinges (option for all ball bearing butt hinges):

- ~ Oil rubbed brass
- ~ Natural brass
- ~ Antique brass
- ~ Polished white bronze
- ~ High polished yellow brass
- ~ Black
- ~ White
- ~ Satin nickel

Phelps sash CSB34 stay with CF222 lever locks with ball bearing butt hinges:

- ~ Oil rub bronze (OB)
- ~ Polished lacquered brass (PB)
- ~ Polished unlacquered brass (PBNL)
- ~ Satin nickel (SN)
- ~ Polished nickel (PN)

SCREENS: (wood swinging) – interior application:

Wood swinging screen in pine or mahogany wood species. Other wood species are available upon request. Hinge & screen knob finishes are limited. Please contact a Norwood sales representative for more information.

SCREENS: (roll down) – interior application:

- ~ Roll down screens are available in all wood species.
- ~ Minimum of 6 9/16" jamb.
- ~ Roll down screens add 7/8" to RO height.
- ~ Norwood recommends the use of a minimum 2 1/2" wide casing for this application

Spec Sheet French Outswing Casement Wood Series



Product Features

GRILLES:

SIMULATED DIVIDED LITE (SDL):

Exterior sdl available in putty & ovalo, interior sdl available in restoration

~ 5/8"

~ 3/4" (putty only for exterior)

~ 7/8"

~ 1 1/4"

~ 1 3/4"

~ 2"

~ 2 1/4"

TRUE DIVIDED LITE:

Contact a Norwood sales representative for prices and availability.

LEAD OVERLAY:

~ 1/4"

~ 3/8"

~ 1/2"

Lead overlay can be applied to one or multiples faces of glass, however, cannot be applied to the low e. Lead overlay is available in patina or silver lead. Custom patterns are available upon request.