

Spec Sheet Rotary Vent Series

Product Features

STANDARD FEATURES (Fixed unit):

- ~ Natural or prime time 2, eastern white pine (clear interior/finger joint exterior)
- ~ Frame construction design for 4 9/16" jambs
- ~ Clear insulated glass
- ~ Choice of black, grey or aluminum spacer bar
- ~ EM600 & 566 subsill

SPECIFICATIONS:

FRAME:

- ~ 1 3/16" thick (overall) X 4 9/16" width/base jamb in pine (or other wood species).
- ~ Jamb extension is available up to 16" wide.
- ~ Frame is manufactured with Bulb weather-strip (white or beige).

SASH:

- ~ 1 5/8" thick in clear pine (or other wood species).
- ~ Interior profiling is ovalo with interior glazing.
- ~ Sash is manufactured with Bulb weather-strip (white or black).

HARDWARE:

Phelps LFD30 handle with locking latch (locking latch available only in PBNL)

- ~ Oil rub bronze (OB)
- ~ Polished lacquered brass (PB)
- ~ Polished unlacquered brass (PBNL)
- ~ Satin nickel (SN)
- ~ Polished nickel (PN)

SCREENS – interior application with wood stop

Black, grey fiberglass mesh & Crystal Clear screen mesh available. Aluminum mesh is not available for this application.